



EAN: 4015474271180
static.hansa.com/01162283



- Washbasin
- Single-lever
- Deck mounted
- Chrome
- Fixed spout
- PCA® - constant flow rate regardless of pressure variations
- Hot/Cold symbols, Single operating lever/handle
- Limitation option for maximum temperature and flow-rate, Adjustable hot water stop (included, retrofittable)
- \varnothing 48 mm ceramic eco cartridge for flow and temperature control
- Flexible inlet pipes
- Inner body made of DZR brass, Rapid installation system
- Without pop-up waste, Without draw-rod opening



Technical data

Flow properties

Eco-flow at 3 bar	4.2 l/min
Flow-rate at 3 bar (with flow controller)	7.8 l/min

Technical properties


DN-size (nominal dimension)	DN15
Hot water supply	max. +70°C
Working pressure	0.5-10 bar
Connection size	G3/8
Projection	127 mm
Backflow prevention (EN1717)	AA
Material	Brass

Regulations


EN standard	EN 817
Noise class	I (ISO 3822)

Approvals and Declarations

KIWA	K6116/08
ABP	P-IX 29886/IA
Declaration of conformity	DoC
EPD	S-P-06391



Spare parts



SP01092283

Name	Code
1 Lever, L=93 mm	01880083
1.1 Screw, M5x8, SW2.5	59904755
1.2 Bushing	59904778
1.3 Symbol plug Grey	59912112
2 Covering cap	59912638
3 Eye screw, M50x1, SW45	59904775
3.1 O-ring, d 43x2.5	59911166
4 Cartridge, 4.8 eco	59904601
4.1 Hot water limiter	59904759
5.1 Pop-up operating rod	59914053
5.2 Swivel joint	59904624
5.3 Bottom seal	59914591
5.5 Fixing plate	59904765
5.6 Screw, M8x1, SW13	59904766
5.7 Fixing set	59910749
5.8 Hose	59912709
5.9 Flexible pipe, L=430, G3/8-M10x1	59912515
5.10 Gasket, 9.5x14.4x2	59912551
5.11 O-ring, d 7.65x1.78	59902337
5.12 Fixing screw, M8x1, L=140	59912474
6 Aerator, M24x1 (2011-)	59913739
7 Pop-up waste	59904620