

EAN: 4015474263994



- Single-lever, side operated
- Chrome
- Swivel spout
- PCA® - constant flow rate regardless of pressure variations, Hidden aerator
- Single operating lever/handle, Hot/Cold symbols
- Litter filter(s), ø 25 mm ceramic cartridge for flow and temperature control
- Inner body made of DZR brass

Technical data

Flow properties

Flow-rate at 3 bar (with flow controller)	6.0 l/min
Pressure loss with flow (0.1 l/s)	2 bar

Technical properties

DN-size (nominal dimension)	DN15
Hot water supply	max. +70°C
Working pressure	1-10 bar
Connection size	G3/8

Regulations

EN standard	EN 817
Noise class	I (ISO 3822)

Spare parts

SP55262203

	Name	Code
1	Lever, 2.5 Chrome	59913985
1.1	Screw, M5x8, SW2.5	59904755
1.3	Symbol plug Grey	59912112
2	Covering cap Chrome	59913957
3	Tightening nut, M32x1, SW24	59913958
4	Cartridge, 2.5	59913914
5.1	Pop-up operating rod Chrome	59913959
5.2	Swivel joint	59904624
5.3	O-ring, 35x2.5	59905020
5.7	Fixing set	59913371
5.8	Flexible pipe, L=430, G3/8-M8x1	59913964
5.9	O-ring, 6x1.4	59913266
5.10	Gasket, 9.5x14.4x2	59912551
6	Swivel spout with ejector Chrome	59913986
6.1	Aerator, M18.5x1, TJ	59913366
6.3	Key for aerator, M18.5	59913367
6.4	Fitting ring for aerator Chrome	59913654
6.6	Screw, M4x7	59902075
6.7	Sealing kit	59911884
7	Pop-up waste Chrome	59904620
8	Cover flange, d 55 mm Chrome	59913963