




EAN: 4057304012228
static.hansa.com/56443203



- Bidet
- Single-lever
- Deck mounted
- Chrome
- Fixed spout
- PCA® - constant flow rate regardless of pressure variations, Ball joint
- Hot/Cold symbols, Single operating lever/handle
- Pop-up waste with draw-rod
- Limitation option for maximum temperature and flow-rate, Adjustable hot water stop (included, retrofittable)
- \varnothing 35 mm ceramic cartridge for flow and temperature control
- Inner body made of DZR brass, 3S-installation system for safe and simple mounting



Technical data

Flow properties

Flow-rate at 3 bar (with flow controller) **6.0 l/min**

Technical properties


DN-size (nominal dimension) **DN15**
 Hot water supply **max. +80°C**
 Working pressure **0.5-10 bar**
 Connection size **G3/8**
 Projection **106 mm**
 Material **Brass**

Regulations


EN standard **EN 817**
 Noise class **I (ISO3822)**

Approvals and Declarations

DVGW **DW-6506CS0548**
 Declaration of conformity **DoC**



Spare parts



SP56443203

	Name	Code
01	Lever	59914712
02	Covering cap, 33x3 mm	59912504
03	Temperature adjustment limiter	59912325
04	Tightening nut, M40x1	1003409V
05	Cartridge, 3.5 Classic	59913075
06	Ball joint for bidet faucet	59910952
07	Aerator, M24x1, 6 l/min	59913727
08	Bottom seal	59914591
09	Fixing screw, M8x1, L=130	59914474
10	Fixing set	59914475